EVORICH[®]

evoFLUTE

Fluted Wall Panels

A sustainable product for interior cladding



WWW.EVORICH.COM.SG

What is evoFLUTE

evoFLUTE is a modern, minimalistic wall panel with a stylish accent.

These timeless styles transform your spaces with their luxurious texture and astonishing detailing.





Installation

Our evoFLUTE are cut with desired precision and are cladded onto the wall with industrial standards adhesive.

(Panels may require screws for reinforcement.)

Care & Maintenance

It is almost hassle-free in cleaning; it requires light dusting with a dry cloth to quickly clean up any dust build-up.

Eco-Friendly

With the appearance and texture of natural wood, no forest and trees are harmed during the process of making evoFLUTE.

evoFLUTE

Available in various colours!



evoFLUTE Colours Collection



Victoria Amber

Code: EFP01 Thickness: 28 mm Dimensions: 220mm x 2800mm





Tensile Cypress

Code: EFP05 Thickness: 28 mm Dimensions: 220mm x 2800mm







Mahogany Americas Code: EFP02 Thickness: 28 mm Dimensions: 220mm x 2800mm





Swedish Pearl Code: EFP06 Thickness: 28 mm Dimensions: 220mm x 2800mm

evoFLUTE Colours Collection



Oak Latte Fishbone Code: EIRP116/CKS156 Thickness: 12.8mm Dimensions: 2800mm x 156mm



Leather Shimmer Fishbone Code: EIRP108/CKS156 Thickness: 12..8mm Dimensions: 2800mm x 156mm





Oak Latte Fishbone

Code: EIRP116/CKS140 Thickness: 13mm Dimensions: 2800mm x 148mm

Leather Shimmer Fishbone

Code: EIRP108/CKS140 Thickness: 13mm Dimensions: 2800mm x 148mm



Oak Latte Fishbone

Code: EIRP116/M100 Thickness: 12mm Dimensions: 2800mm x 99.59mm

Leather Shimmer Fishbone

Code: EIRP108/M100 Thickness: 12mm Dimensions: 2800mm x 99.59mm

White Leather

Code: PF995/M100 Thickness: 12mm Dimensions: 2800mm x 99.59mm

evoFLUTE Specifications

COMPOSITION

Dimension	220*26*2900mm
Weight	8.07kg Per Pc
Layer Part	100% Engineered Plastic
Core Part	35% Plastic, 55% Wood Fiber & 10% Additives

PHYSICAL PROPERTIES

Abrasion Resistance	9.3mg
Water Absorption	0.30%
UV1500h:	$\Delta^{E=1.3}$
Mildew Proof (ASTM)	0
Liner Thermal Expansion Coefficient (-20oC ~ 80oC)	35.1x10-6 1/oC
Rate of Elastic Recovery	72%













- **L** +65 6348 7333
- ➡ sales@evorich.com.sg
- +65 6342 9331
- **G@** @evorichflooring

WhatsApp us at +65 8795 2118

www.evorich.com.sg

- Evorich R&D Production Experience Exhibit (Cheques Receiving Centre): 16 Tampines Street 92 Singapore 528873
- **EVORICH Concept Sales Gallery** Floors • Decks • Walls • Ceilings:

1 Tampines North Drive 1 02-38 T-Space, Evorich Block, Singapore 528559

EVORICH Floors • Deck • Walls Training Academy:
27 Kim Chuan Terrace Singapore 537045